

Timber Sale Appraisal Cost Summary Wolf's Foot Sale 341-03-30

District: Tillamook

Date: 5/9/03

	Conifer	Hardwood	Total
Gross Timber Sale Value	\$1,699,596.60	\$0.00	\$1,699,596.60
		Project Work	(\$205,198.10)
	A	dvertised Value	\$1,494,398.50



Timber Sale Appraisal Timber Description Wolf's Foot Sale 341-03-30

"STEWARDSHIP IN FORESTRY"

District: Tillamook

Location: Sections 7,18, T1N, R7W, and Section 13, T1N, R8W, W.M., Tillamook County, Oregon

Date: 5/9/03

Stand Stocking: 40%

Species	Avg. DBH	Amortized%	Recovery%
Douglas - Fir	14	0	95

Volume by Grade	Douglas - Fir	Total		
28	1,670	1,670		
38	4,521	4,521		
48	583	583		
Total	6,774	6,774		

Comments: Pond Values Used: 1st Quarter 2003 + Local Pond Values

See additional cost sheet for additional P&R and Road Maintenance.

Hardwood pond value of \$515/MBF was obtained locally in March 2003. Hardwood stumpage: \$515/MBF - \$255.96 logging cost = 259.04



Timber Sale Appraisal Logging Conditions Wolf's Foot Sale 341-03-30

"STEWARDSHIP IN FORESTRY"

Combination#: 1

Douglas - Fir

87.39%

Yarding Distance: Medium (800 ft)

Downhill Yarding No

Logging System:

Cable: Medium Tower >40 - <70

Process: Manual Delimbing

Tree Size:

Small / Thinning 12in (130 Bft/tree), 12-17 logs/MBF

Loads/Day:

7

Bd. Ft./Load: 3,400

Cost/MBF:

\$139.35

Machines:

Log Loader (A)

Tower Yarder (Medium)

12.61%

Combination#: 2

Douglas - Fir

Downhill Yarding Yes

Logging System:

Yarding Distance: Short (400 ft) Track Skidder

Process: Manual Falling/Delimbing

Tree Size:

Small / Thinning 12in (130 Bft/tree), 12-17 logs/MBF

Loads/Day:

Bd. Ft./Load: 3,400

Cost/MBF: \$120.05

Machines:

Log Loader (B) Track Skidder



Timber Sale Appraisal Logging Costs Wolf's Foot Sale 341-03-30

"STEWARDSHIP IN FORESTRY"

Date: 5/9/03

Operating Seasons: 2.4

Profit & Risk: 20%

Project Costs: \$205,198

Other Costs (P/R): \$17,508

Slash Disposal: \$0

Other Costs: \$8,126

	Miles	of Road	
Dirt	Rock (Contractor)	Rock (State)	Paved
0.0	0.0	0.0	0.0

Road Maintenance: \$0.96

Hauling Costs

Species	\$/MBF	Trips/Day	MBF/Load
Douglas - Fir	\$0.00	2.0	3.4

Local Pond Values

Date	Species	Grade	Value
5/9/03	Douglas - Fir	2S	\$530.00
5/9/03	Douglas - Fir	38	\$505.00
5/9/03	Douglas - Fir	4S	\$455.00



Timber Sale Appraisal Logging Costs Breakdown Wolf's Foot Sale 341-03-30

Costs	Douglas - Fir
Logging	136.92
Road Maintenance	1.01
Fire Protection	0.96
Hauling	69.16
Other (P/R appl.)	2.58
Profit & Risk	42.13
Slash Disposal	0.00
Scaling	2.00
Other	1.20

Amortization	0.00
Pond Value	506.86
Stumpage	250.90
Amortized	0.00

Total

255.96



Timber Sale Appraisal Summary Wolf's Foot Sale 341-03-30

"STEWARDSHIP IN FORESTRY"

	Douglas - Fir
МВГ	0.00
Value	0.00
Total	0.00

Unamortized

	Douglas - Fir
MBF	6,774.00
Value	250.90
Total	1,699,596.60

Gross Timber Sale Value

Recovery \$1,699,596.60

Prepared by: Tod Haren

Date: 5/9/03

District: Tillamook

Phone: (503) 842-2545



Timber Sale Appraisal Additional Cost Worksheet Wolf's Foot Sale 341-03-30

Cable Yarding Vol. (MBF): 5920 Ground Yarding Vol. (MBF): 854 Total Sale Volume: 6774

	ADDITIONAL	COSIS-P	ROFIT & F	KISK IIOJE	ie addel)	
Yarding & Loading:			Cost / MB	.	Volume (MBF)	
Brand &	Paint:		\$ 2	Х	6774		\$13,548
Truck As	sist/Tractor Swir	ng .	\$ 30	X	132		\$3,960
			Cost / Eac	h 01	HER CO	STS TOTAL	\$17,508
	ADDITIONA	L COSTS -	PROFIT 8	RISK IN	ONUDED		
Non-Project Roads	(See Logging Pl	an in Cruise	Report)				
Non-Proj.	Rd. 1	17	Stations	X	\$ 90		\$1,530
Swing Ro	ad "A"	3	Stations	X	\$ 90		\$270
	Totals	20					\$1,800
		Stations	×	cys	×	\$/cy	
Approach Rock:	Pit-Run	3		50	X	\$6.00	\$900
Bank Slough/Minor	Slides/Catch Ba	sins (per CY)•	\$ 19	X	150	\$2.850
OHV Trail Clearing	(per station)			\$ 40	X	4.4	\$176
Dust Abatement (pe	and the state of t			\$ 1,200		2	\$2,400
<u> </u>					<u> </u>	STS TOTAL	\$8,126
			ROAD M	AINTENA	NCE		
			\$/Cu.Y	MMBF	Miles	cu.yds/mile	\$/MBF
	Surfacing ³ :	Pit-Run	\$6.00	6.8	4.5	25	\$0.68
		Crushed	\$18.00	6.8	0.4	25	\$0.18
			\$/Mile	MMBF	Miles		

¹Includes cost for excavating, and hauling material from bank slough and minor slides(50 cys)

500

6.8

TOTAL ROAD MAINTENANCE COST / MBF

0.4

\$0,10

\$0.96

Grading⁴

²Cost for lignin sulfonate application as dust abatement material.

³Assumes 25 cys rock per MMBF per mile

⁴Grading once per 2 MMBF hauled

PROJECT SUMMARY SHEET

Sale: WOLF'S FOOT

CONSTRUCTION

Point	A to B	27+65	stations =	\$21,649.48						
Point	C to D	7+30	stations =	\$4,404.82						
		0115								
		SUE	STOTAL CONSTRUCTION	\$26,054.30						
IMPROVE	IMPROVEMENT									
Point	A to B	180+10	stations =	\$141,015.23						
Point	C to D	29+60	stations =	\$17,860.65						
Point	E to F	14+00	stations =	\$15,861.75						

	SUBTOTAL IMPROVEMENT	\$174,737.64
SPECIAL PROJECTS		
Remove Culverts from State Lar	nds	\$326.07
S	UBTOTAL SPECIAL PROJECTS	\$326.07
MOVE IN		\$4,080.10
	GRAND TOTAL	\$205,198.10

Sale:	WOLF'S FOOT				Road: A to B	-	
Construction -	27+65 0.52	stations miles			Improvement -	180+10 stations 3.41 miles	
CLEARING AND GRUBBING - Roadside Brushing Side cast Widening Scattering Piling Endhaul			0.048 0.101 9.150 0.000	miles @ acres @ acres @ acres @ acres @ acres @	\$1,000.00 per mile = \$540.00 per acre = \$540.00 per acre = \$815.00 per acre = \$905.00 per acre = \$1,500.00 per acre =	\$0.00 \$0.00	
EXCAVATION - Road Earthwork Road Earthwork Road Earthwork Road Earthwork Widening Pullback Remove outside berm Slope Stabilization Prep. Slope Stabilization Prep. Full Bench Widening/Full Bench			21.50 135.80 20.80 27.65 1437 139 130 70 19 2665 2233	sta. @ sta. @ sta. @ sta. @ cy. @ cy. @ cy. @ cy. @ cy. @	\$0.00 per sta. = \$20.00 per sta. = \$65.00 per sta. = \$85.00 per sta. = \$1.40 per c.y.= \$1.40 p	\$0.00 \$2,716.00 \$1,352.00 \$2,350.25 \$2,011.80 \$194.60 \$182.00 \$98.00 \$60.80 \$3,731.00 \$3,126.20	\$8,636.33 \$15,822.65
ENDHAUL - Widening Pullback Remove outside berm Slope Stabilization Prep. Full Bench Widening/Full Bench Spread & compact			1437 139 130 89 2665 2233 6693	cy. @ cy. @ cy. @ cy. @ cy. @ cy. @	\$0.92 per c.y.= \$0.94 per c.y.= \$0.95 per c.y.= \$1.02 per c.y.= \$1.40 per c.y.= \$1.10 per c.y.= \$0.35 per c.y.=	\$1,322.04 \$130.66 \$123.50 \$90.78 \$3,731.00 \$2,456.30 \$2,342.55 AL ENDHAUL	\$10,196.83
CULVERTS - MATERIALS & INS	ALLATION Culverts						
	42 LF of 0 LF of 82 LF of 0 LF of 0 LF of	30" 42" \$ 54" 66"	\$619.50 \$0.00 \$2,492.70 \$0.00 \$0.00		78 LF of 24" 42 LF of 36" 60 LF of 48" 52 LF of 60" 0 LF of 72"	\$1,384.50 \$1,155.70 \$3,833.10 \$3,311.70 \$0.00 \$9,685.00	
	Half Rounds 0 LF of	21"	\$0.00		0 LF of 30"	\$0.00	
	0 LF of <u>Culvert Stakes &</u>		\$0.00		0 LF of 42"	\$0.00 \$0.00	
	0 stakes 8 markers		\$0.00 \$48.00 \$48.00		TOTA	L CULVERTS	\$12,845.20
SURFACING- 0+00 to 21+1: 21+15 to 183+ 183+75 to 207+ 81+05 Bedding/backfill Riprap slope stabilization Riprap slope protection Riprap energy dissipator Riprap energy dissipator Riprap subgrade protection Riprap subgrade protection Riprap subgrade protection Riprap subgrade protection Pit-run stabilization Pit-run culvert backfill Pit-run ditch/emb. fill	5 11,847 cy. of	Pit-Run Pit-Run Crushed Riprap		9999999999999	\$18.05 per c.y.= \$6.00 per c.y.= \$5.95 per c.y.= \$19.40 per c.y.= \$6.92 per c.y.= \$6.93 per c.y.= \$6.94 per c.y.= \$6.95 per c.y.=	\$9,564.38 \$71,082.00 \$8,199.10 \$775.87 \$1,937.60 \$138.40 \$346.00 \$429.60 \$136.80 \$62.40 \$485.16 \$124.40 \$746.40 \$311.00	\$94,4 05.31
SPECIAL PROJECTS Re-shape dented culvert inlet - Remove gate assembly - Construct waste areas - Construct ditchouts - Fill roadway @ area of 127+80 - Fill ditch/emb from 128+50 to 129+ Remove log cribbing @ 166+70 - Grade and shape road - Construct/Install rubber water diver Subgrade protection areas - Roll subgrade w/ vibratory roller pri Remove log culvert @ stations: 81- Remove large stumps - Grass seed and fertilize - Mulching -	er - or to rocking -	-	13.00	hours @ hours @ hours @ hours @ hours @ stations @ o stations @ hours @ acres @ acres @	\$28.00 per hour \$88.00 per hour \$130.00 per hour \$130.00 per hour \$130.00 per hour \$130.00 per hour \$14.20 per station \$300.00 each \$153.47 each \$11.00 per station \$130.00 per hour \$130.00 per hour \$130.00 per acre \$1,000.00 per acre	\$28.00 \$44.00 \$910.00 \$780.00 \$325.00 \$195.00 \$65.00 \$2,950.05 \$5,400.00 \$460.41 \$2,285.25 \$1,690.00 \$1,403.58 \$2,347.11	\$20,758.39

SUMMARY OF CONSTRUCTION COST

ENDHAUL - Widening/Full Bench	Sale:	WOLF'S FOOT		Road:	C to D		
Side cast	Construction -			Improveme	ent -		8
EXCAVATION	Side cast Widening Scattering Piling	NG -	0.00 acres 3.398 acres 0.00 acres	\$ @ \$540.00 \$ @ \$815.00 \$ @ \$905.00 \$ @ \$1,500.00	o per acre = o per acre = o per acre = o per acre =	\$0.00 \$2,769.05 \$0.00 \$0.00	\$2.760.0E
Widening/Full Bench 2+30 to 6+70 1083 cy.	Road Earthwork Drift Road Earthwork Road Earthwork Drift Road Earthwork	11+50 to 14+15 14+15 to 17+00 17+00 to 22+90 22+90 to 25+90	2.7 sta. 2.9 sta. 5.9 sta. 3.0 sta. 11.0 sta.	 \$65.00 \$125.00 \$65.00 \$85.00 \$125.00 \$85.00 \$85.00 	O per sta. = O per c.y.=	\$747.50 \$331.25 \$185.25 \$501.50 \$375.00 \$935.00 \$630.00	\$3,705.50
CULVERTS - MATERIALS & INSTALLATION Culverts 0	Widening/Full Bench Widening/Full Bench	11+50 to 12+80	40 cy.	@ \$0.9	6 percy.=	\$38.48	
Culverts					ť	OTAL ENDHAUL	\$1,097.76
\$0.00 \$0.00 \$0.00 Culvert Stakes & Markers \$0.00 \$0.00 0 stakes \$0.00 \$0.00 0 markers \$0.00 \$0.00 0	CULVERTS - MATERIALS	Culverts 0	\$0.00 \$0.00 \$0.00 \$0.00 \$0.00		0 LF of 36" 0 LF of 48" 0 LF of 60" 0 LF of 72"	\$0.00 \$0.00 \$0.00 \$0.00 \$0.00	
0+00 to 36+90 2,002 cy. of Pit-Run @ \$6.09 per c.y.= \$12,192.18 TOTAL SURFACING \$12,192 \$PECIAL PROJECTS Construct waste area @ 8+50 - Construct waste area @ 26+65 - Remove large stumps - Grade and shape road - Fill roadway @ area of 24+90 - \$6.00 Per c.y.= \$12,192.18 TOTAL SURFACING \$12,192 \$130.00 per hour \$65.00 \$65.00 \$687.50 \$687.50 \$14.20 per station \$523.98 \$130.00 per hour \$325.00		<u>Cuivert Stakes & Markers</u> 0 stakes	\$0.00 \$0.00 \$0.00	'		\$0.00	\$0.00
SPECIAL PROJECTS 0.50 hours @ \$130.00 per hour \$65.00 Construct waste area @ 26+65 - Construct waste area @ 26+65 - 1.00 lump sum @ \$130.00 per hour \$65.00 \$687.50 \$687.50 Remove large stumps - Grade and shape road - 5lil roadway @ area of 24+90 - 2.50 hours @ \$130.00 per hour \$325.00 \$130.00 per hour \$523.98		0 2,002 cy. of Pit-Run	@	\$6.09	per c.y.=	\$12,192.18	
Grass seed and fertilize - 2.38 acres @ \$180.00 per acre \$428.60	Construct waste area @ 8+: Construct waste area @ 26- Remove large stumps - Grade and shape road - Fill roadway @ area of 24+9 Roll subgrade w/ vibratory ro	+65 - 90 -	0.50 hours 1.00 lump su 36.90 station 2.50 hours 36.90 stations	@ \$130.00 m @ \$687.50 s @ \$14.20 @ \$130.00 @ \$11.00	o per hour o per hour o per station o per station o per station o per acre	\$65.00 \$65.00 \$687.50 \$523.98 \$325.00 \$405.90 \$428.60	\$12,192.18 \$2,500.98

GRAND TOTAL \$22,265.47

SUMMARY OF CONSTRUCTION COST

Sale:	WOLF'S F	оот				Road:	E to F		
Construction -		0+00	_stations			Improvemen	t -	14+00	stations
CLEARING AND GRUBBING - Side cast Widening Scattering Piling Endhaul EXCAVATION -	3690.00	0.00	_miles	0.00 0.040 0.00	acres 6 acres 6 acres 6 acres 6	\$540.00 \$815.00 \$905.00 \$1,500.00	per acre = TOTAL CLEAF	\$0.00 \$0.00 \$32.60 \$0.00 \$0.00 \$1.00	_
	+00 to	14+00		4.0	sta. @	\$0.00	per sta. =	\$0.00	
						,		Viii	
								TOTAL EXCAVATION	\$0.00
ENDHAUL -									
Culvert excavation to waste area Place and compact				450 450	cy @o		7 per cy 5 per cy	\$302.16 \$157.50	
								TOTAL ENDHAUL	\$459.66
CULVERTS - MATERIALS & INSTALLATION	Culverts 0 0 0 0 0 0 Half Rounc	LF of 21	· ·	\$0.00 \$0.00 \$0.00 \$0.00 \$0.00 \$0.00 \$0.00 \$0.00		((102	D LF of 24 D LF of 36 D LF of 48 D LF of 103*x D LF of 103*x	\$0.00 \$0.00 \$0.00 \$11,643.20 \$11,643.20 \$30* \$0.00	_
	0	stakes markers		\$0.00 \$0.00 \$0.00				TOTAL CULVERTS	\$11,643.20
SURFACING- 1+00 to 3+00 and 12+00 to 14+00 Riprap fill armor (from Hwy pit) - Culvert bedding/backfill (from Ceder Ck Stockpile) In-Stream Riprap placement @ outlet	88 130 310 20	cy. of cy. of cy. of cy. of	Crushed Riprap (12*-24*) Crushed Riprap (24*-48*)		0 0 0 0	\$5.11 \$2.93	per c.y.= i per c.y.= i per c.y.= per c.y.=	\$1,767.31 \$663.83 \$906.86 \$102.13 TOTAL SURFACING	
SPECIAL PROJECTS Grade and shape road - Roll subgrade w/ vibratory roller prior to rocking - Grass seed and fertilize - Mulch (@ culvert area) -			,	4.00 0.52	stations © stations © acres © acres ©	\$11.00		\$39.00 \$44.00 \$92.98 \$110.19 SPECIAL PROJECTS	_

CRUSHED ROCK PIT DEVELOPMENT COST SUMMARY

	Pit:	COMMERC	IAL SOURCE	:	Location:	TILLAM	OOK	COUNTY	
	Sale:	WOLF'S FO	OT	_	Road:			658 c.y.	······································
	Swell:	1.30	- 4	- <u>.</u>	Stockpile:			c.y.	
	Shirinkage	1.16		-	Total Truck	Loads:	_	658 c.y.	
	Drill Pct.:	0%		-	In Place To	tal:		506 c.y.	
	Road Brushi	ing:	0	acres @	\$905.0	0 per acre	=	\$0.00	
	Clear and gr	ub	0	acres @	\$815.0	0 per acre	=	\$0.00	
	Drill & Shoot	t:		/cu,yd. >		0 cu.yds.		\$0.00	
	Push Rock:			_/cu.yd. >		0 cu.yds.		\$0.00	
	Load crushe	er:		/cu.yd. >		0 cu.yds.		\$0.00	
	Crushing			/cu.yd. x		0 cu.yds.		\$0.00	
	Load Dump	Truck:	\$0.60	/cu.yd. x	·	0 cu.yds.	_	\$0.00	
						Subt	total	\$0.00	
	Purchase 1	1/2"-0" Crushe	ed Rock from	Commercia	al Source			\$5,101.83	
								\$0.00	
								\$0.00	
								\$0.00	
								\$0.00	
								\$0.00	
								\$0.00	
						Subt	total	\$0.00 \$0.00	
								\$0.00 \$0.00 \$0.00	\$5,101.8
1 1/2"-0" Crush	ed Base Cost=	\$7.75	Per Cu.Yd.					\$0.00 \$0.00 \$0.00 \$5,101.83	\$5,101.8
1 1/2*-0* Crusho Road	ed Base Cost⊨ Haul Cost	\$7.75 Proc Cost	Per Cu.Yd.	Cost	Number			\$0.00 \$0.00 \$0.00 \$5,101.83	\$5,101.8
			-	Cost /cu.yd				\$0.00 \$0.00 \$0.00 \$5,101.83 DUCTION COSTS	\$5,101.8
Road	Haul Cost	Proc Cost	Base Cst.					\$0.00 \$0.00 \$0.00 \$5,101.83 DUCTION COSTS	\$5,101.8
Road Segment A to B	Haul Cost /cu.yd.	Proc Cost /cu.yd.	Base Cst. /cu.yd.	/cu.yd	. Cu. Yds			\$0.00 \$0.00 \$0.00 \$5,101.83 DUCTION COSTS	\$5,101.8
Road Segment A to B	Haul Cost /cu.yd. \$8.52	Proc Cost /cu.yd. \$1.78	Base Cst. /cu.yd. \$7.75	/cu.yd \$18.05	Cu. Yds 530			\$0.00 \$0.00 \$0.00 \$5,101.83 DUCTION COSTS ROCK COST \$9,569.79	\$5,101.8
Road Segment A to B A-B Culvert bedding	Haul Cost /cu.yd. \$8.52 \$11.05	Proc Cost /cu.yd. \$1.78 \$0.60	Base Cst. /cu.yd. \$7.75 \$7.75	/cu.yd \$18.05 \$19.40	530 40		PRC	\$0.00 \$0.00 \$0.00 \$5,101.83 DUCTION COSTS ROCK COST \$9,569.79 \$775.87	\$5,101.8
Road Segment A to B A-B Culvert bedding	Haul Cost /cu.yd. \$8.52 \$11.05	Proc Cost /cu.yd. \$1.78 \$0.60	Base Cst. /cu.yd. \$7.75 \$7.75	/cu.yd \$18.05 \$19.40	530 40 88	TOTAL	_ PRO	\$0.00 \$0.00 \$5,101.83 DUCTION COSTS ROCK COST \$9,569.79 \$775.87 \$1,767.31	\$5,101.8 \$12,112.9

ROCK DEVELOPMENT COST SUMMARY

	Pit: Pit-Run Sale: WOLF'S F Swell: 1.30 Shirrinkage 1.16 Drill Pct.: 75%	ООТ	Location: Road: Stockpile B Total Truck In Place To	Loads:	: 13, T1N, R8W, W 15945 c.y. c.y. 15945 c.y. 12265 c.y.	/.M.
					\$2,248.00	
	Drill and Shoot	\$2,10 /cu.y	/d. x 9199	cu.yds. =	\$19,317.98	
	Rip Rock	\$1.75 /cu.y	/d. x 3536	cu.yds. =	\$6,188,44	
	Push Rock	\$0.60 /cu.y		cu.yds. =	\$9,567.00	
	Load Dump Truck:	\$0.60 /cu.y		cu.yds. =	\$9,567.00	
	Stockpile Oversized	\$1.40 /cu.y	/d. x 1595	cu.yds. =	\$2,232.30	
				Subtotal	\$49,120.72	
	Move in Drill & Compres	ssor			276.58	
	Move in Loader				391.46	
	Move in D8				433.09	
	Move in Roller				276.58	
	Move-in Trucks -				182,40	
				Subtotal	\$1,560.11	
	Base Cost= \$3.18	Per Cu.Yd.	[TOTAL PRODUC	CTION COSTS	\$50,680.83
Road	Haul Cost Proc Cost	Base Cet (Cost Number		ROCK	
Segment	/cu.yd. /cu.yd.		cu.yd. Cu. Yds		COST	
A to B (12" lift)	\$1.92 \$0.90		6.00 11847	-	\$71,082.00	
A to B (9" lift)	\$1.87 \$0.90		5.95 1378	-	\$8,199.10	
C to D (9" lift)	\$2.01 \$0.90		6.09 2002	-	\$12,192.18	
Riprap A to B	\$2.34 \$1.40		6.92 350	-	\$2,422.00	
Riprap A to B	\$2.58 \$1.40	\$3.18	7.16 60	-	\$429.60	
Riprap A to B	\$2,26 \$1.40		6.84 20		\$136.80	
Riprap A to B	\$2.04 \$1.40		6.62 10	•	\$66.20	
Riprap A to B	\$1.67 \$1.40	\$3.18	6.24 10	-	\$62.40	
Addison Division A.A. D	A4 (4 A4 4A	A		-		

Misc. Pit-run A to B

\$1.40

\$1.64

\$3.18

\$6.22

Total C.Y.

268

15945

TOTAL ROCKING COSTS

Sub Total \$94,461.68

\$1,666.96

\$94,461.68

CRUSHED ROCK PIT DEVELOPMENT COST SUMMARY

	Pit:	CEDER CR			Location:	NE 1/4,	NW 1/	4 SEC 7, T1N, R7W, W	.M.
	Sale:	WOLF'S FC	ОТ	•	Road:			310 c.y.	
	Swell:	1.30		,	Stockpile:			c.y.	
	Shirinkage	1.16		•	Total Truck			310 c.y.	
	Drill Pct.:	0%			In Place Tot	al:		238 с.у.	
	Road Brushi	ng:	0	acres @	\$905.0	per acre) =	\$0.00	
	Clear and gr	ub	0	acres @	\$815.00	per acre	=	\$0.00	
	5.11.0.01		A 2.10						
	Drill & Shoot	:		/cu.yd. x		cu.yds.		\$0.00	
	Push Rock:			/cu.yd. x		cu.yds.		\$0.00	
	Load crushe	r:		/cu.yd. x		cu.yds.		\$0.00	
	Crushing			/cu.yd. x		cu.yds.		\$0.00	
	Load Dump	Truck:	\$0.60	/cu.yd. x		cu.yds.		\$0.00	
						Sub	lotal	\$0.00	
	Load 1 1/2"-	0" Crushed Re	ock from stock	pile				\$0.00	
								\$0.00	
								\$0.00	
								\$0.00	
								\$0.00	
								\$0.00	
								\$0.00	
								\$0.00	
						Sub	lotal	\$0.00	
						TOTAL	L PRO	DUCTION COSTS	\$0.0
1 1/2"-0" Cru	shed Base Cost=	\$0.00	Per Cu.Yd.					,,,,,,	
Road	Haul Cost	Proc Cost	Base Cst.	Cost	Number			ROCK	
Segment	/cu.yd.	/cu.yd.	/cu.yd.	/cu.yd.	Cu. Yds	_	_	COST	
E to F	\$2.33	\$0.60	\$0.00	\$2.93	310			\$906.86	
				,	310	_ Subtot	tal —	\$906.86	

MOVE-IN CALCULATIONS

Sale: WOLF'S FOOT

LOWBOY HAUL (Round Trip)								
DISTANCE	ROADWAY	AVE SPEED (MPH)						
	Highway	40						
1.2	Main Lines (Off Road)	10						
0.0	Pulling Steep Grades	2						

Г	EQUIPMENT	Move in	Pilot	Within Area Move	Begin	End	Total	Within Area	Total
No.	DESCRIPTION	Cost	Cars	(\$/mile)	Mileage	Mileage	Miles	Cost	Cost
1	Drill & Compressor	\$189.17		\$46.00	0.00	3.01	3.0133	\$138.61	\$327.78
1	Brush Cutter	\$189.17		\$4.00	0.00	1.10	1.1	\$4.40	\$193.57
2	Graders	\$183.62		\$3.65	0.00	3.01	3.0133	\$22.00	\$205.62
0	Loader (Small)	\$0.00	1	\$3.55	0.00	1.67	1.6686	\$0.00	\$0.00
1	Loader (Med. & Large)	\$261.49	1	\$9.00	0.00	0.00	0	\$0.00	\$261.49
2	Rollers & Compactors	\$378.34		\$5.00	0.00	3.01	3.0133	\$30.13	\$408.47
0	Excavators (Small)	\$0.00		\$22.00	0.00	0.00	0	\$0.00	\$0.00
1	Excavators (Med.)	\$223.59		\$35.50	0.00	3.01	3.0133	\$106.97	\$330.56
3	Excavators (Large)	\$872.03	1	\$44.80	0.00	1.67	1.6686	\$224.25	\$1,096.28
1	Rubber Tired Backhoes/Skidders	\$189.17		\$3.00	0.00	1.73	1.7254	\$5.18	\$194.34
0	Tractors (D6)	\$0.00	2	\$7 .10	0.00	0.00	0	\$0.00	\$0.00
1	Tractors (D7)	\$280.12	2	\$11.30	0.00	1.73	1.7254	\$19.50	\$299.61
1	Tractor (D8)	\$291.79	2	\$15.10	0.00	1.67	1.6686	\$25.20	\$316.99
2	Dump Truck (10 cy +)	\$115.75		\$2.85	0.00	7.01	7.0133	\$39.98	\$155.72
1	Dump Truck (Off Hiway)	\$223.59	1	\$ 4.75	0.00	1.73	1.7254	\$8.20	\$231.79
1	Water Truck (1500 Gal)	\$57.87		\$2.85	0.00	0.00	0	\$0.00	\$57.87
0	Water Truck (2500 Gal)	\$0.00		\$2.85	0.00	0.00	0	\$0.00	\$0.00
0	Jaw	\$1,066.00							
0	2-Stage Crusher	\$1,597.00							
0	3-Stage Crusher	\$2,489.00							

L	TOTAL MOVE-IN	COSTS:	\$4,080.10



OREGON DEPARTMENT OF FORESTRY CRUISE REPORT Wolf's Foot

1. Type of Sale

Partial Cut/Clearcut - Recovery

2. Legal Description

Portions of Section 13,T1N, R8W, Sections 7,18, T1N, R7W, W.M. Tillamook County, Oregon

3. Sale Acreage

Sale acreage was determined by plotting posted boundaries in ArcView GIS, using digital orthophotos and planimetric themes.

	ACRES					
	<u>Sale</u>	<u>Total</u>	<u>Net</u>			
Area 1 (Clearcut)	116	122	114			
Area 2 (Clearcut)	60	55	55			
Area 3 (Partial Cut)	164	155	155			
Area 4 (Clearcut)	32	36	32			
Area 5 (Partial Cut)	17	16	16			
Area 6 (Clearcut)	32	30	30			
Total	421	414	402			

Sale Acres

Area within the Timber Sale Boundary signs

Total acres

For accomplishment reporting

Clearcut harvest - Sale acres; plus green tree retention acres outside the sale boundary; less roads and riparian areas classified as Special Stewardship in LMCS inside the sale boundary.

Partial Cut - Sale acres less areas of low stocking, hardwoods, roads, and riparian areas classified as Special Stewardship in LMCS inside the sale boundary.

Net acres

Used for calculating the advertised volume.

Clearcut - Sale acres, less green tree retention, roads, and riparian areas classified as Special Stewardship in LMCS inside the sale boundary.

Partial Cut - Same as total acres

4. Cruising Procedures

A. Cruise Method

Seven cruise lines were established throughout the sale areas, parallel lines were spaced 17 chains apart. Line starting points were located using aerial photographs. 63 sample points were located along these lines using a compass and a rangefinder, or pacing. Sample points were spaced three chains apart. Sample trees were selected using a Relaskop. All selected trees were measured for DBH to the nearest inch.

A sub-sample was chosen at each point to estimate VBAR. At least the first two

Douglas-fir, clockwise from the line and a tree from other species were chosen for the volume sub-sample. Measurements for volume included DBH (nearest tenth inch), form factor at 16', height to a 6" merchantable top (8" for alder), and grades and lengths of each segment. The minimum saw log piece size was 30 b.f.

B. Plot size

A 28 BAF (27.78 relaskop) was used for tree selection at each point; Point of observation was at 4.5 feet.

C. Grading System

Trees were graded following the Columbia River Official Log Scaling and Grading Bureau rules.

5. Computation Procedure

Stand tables and tree volumes(V-BAR) were calculated with the SuperACE cruise program. Volume per acre was calculated by multiplying the estimated take BA per acre times the VBAR. Estimated take BA per acre was derived from the stand table. For Areas 3 and 5, 40 sq. ft. of BA was subtracted from the current stand BA. For Areas 1, 2, 4, and 6, the take BA was the sum of all the diameter classes less than 21 inches DBH.

6. <u>Hidden Defect and Breakage</u>

A five percent reduction was applied to the calculated volume to account for hidden defect and breakage. Visible defect was deducted while cruising.

7. Timber Description

The entire sale area burned in both the 1933 and 1939 Tillamook fires. The stand consists primarily of Douglas-fir planted in 1950, and red alder in the draws and on old landings. A few hemlock, spruce, and cedar are scattered through the sale area. The average Douglas-fir merchantable bole length was 64 feet.

8. Cruiser Names/Dates

Tod Haren, Dave Wells, Barb Moore: 04/23/2002 - 04/25/2002

9. Revenue Distribution

100% FDF

Tax Code: 56(59%), 9-2(41%)

Deed Numbers: 138, 157, 159, 161, 162, 194

100% Rehabilitation Obligated

10. Attachments

Volume Summary

Stand Table

VBAR Summary

Logging Plan

X:\StateForests\CentralUnit\Timber Sale Folders\2002 Sale Plan\Wolfs Foot\Documents\WF_Cruise Report.doc



Timber Sale Appraisal Volume Summary Wolf's Foot Sale 341-03-30

"STEWARDSHIP IN FORESTRY"

			231	acres		
SPECIES			Vel/site Velici	∰Gross MBF	D. 8 B	Net Vol MBF
Douglas-fir	181	103.7	18.8	4343	5%	4126
TOTAL	181		18.8	4343		4126

Area 3, 5 P	C (Lea	ve 35 -	45 BA)	er i se direktioner	er læfig er	28 d.s.
			171	acres		
SPECIES	Basaí Area	Y.e.A.r	VoVAcre MBF	Volume MBF	D & B	Net Vol MBF
Douglas-fir	154	105.8	16.3	2787	5%	2648
TOTAL	154		16.3	2787		2648

TOTAL SA	LE VOLUME	
	402	acres
SPECIES	MBF	MBF NET
Douglas-fir	7130	6774
TOTAL	7130	6774

тс	TS	TNDSUM	1		Stand Tab	le :	Summa	ry	· · · · · · · · · · · · · · · · · · ·		i	
					Project		W FOOT					
					-	AII	Areas					
T1N F	77W	S18 T	STND		Tract		Туре	Twp	Rge	Sec	··	
			Acres 415.00	Plots 63	STAND INFO Sample Tree 458		STND	1N	7W	18	Page: Date: Time:	1 1/7/03 1:54:19PM
									Cumu	latives		ſ
	s		Sample	FF	Trees	s/	BA/	TI	PA		BA	
Spc	T	DBH	Trees	16	Acre		Acre	+	-	+	-	
DF		8	2	89		2.55		2.55		0.89		
DF		9	8	88	ŀ	8.05	3.56	10.59		4.44		
DF		10	22	89	1	7.93	9.78	28.52		14.22		
DF		11	21	88	1	4.14	9.33	42.66	145.23	23.56		
DF		12	37	89	2	0.94	16.44	63.60	131.09	40.00	170.67	
DF		13	42	88	2	0.25	18.67	83.85	110.15	58.67	154.22	
DF		14	48	88	1	9.96	21.33	103.81	89.90	80.00	135.56	
DF		15	48	88	1	7.38	21.33	121.19	69.94	101.33	114.22	
DF		16	48	89	1:	5.28	21.33	136.47	52.56	122.67	92.89	
DF		17	42	88	1	1.84	18.67	148.31	37.28	141.33	71.56	
DF		18	38	89	,	9.56	16.89	157.87	25.44	158.22	52.89	1.0
DF		19	29	88	j,	6.55	12.89	164.42	15.88	171.11	36.00	700
DF		20	23	89] ,	4.69	10.22	169.10	9.34	181.33	23.11	
DF		21	7	89	1	1.29	3.11	170.40	4.65	184.44	12.89	
DF		22	10	88		1.68	4.44	172.08	3.36	188.89	9.78	
DF		23	4	89		0.62	1.78	172.70	1.67	190.67	5.33	
DF		24	3	88		0.42	1.33	173.12	1.06	192.00	3.56	
DF		25	3	88		0.39	1.33	173.51	0.63	193.33	2.22	
DF		26	2	89		0.24	0.89	173.75	0.24	194.22	0.89	
DF		Totals	437	88	17:	3.75	194.22	1				
RA		9	1	87		1.01	0.44					
RA		10	1	87	(0.81	0.44	X	10:1			
RA		11	1	86	(0.67	0.44		177	1		
RA		12	3	86		1.70	1.33		LUM	Y	\smile	
RA		13	2	87		0.96	0.89		75	•		
RA	ł	14	1	86	(0.42	0.44		154			
RA		15	3	86		1.09	1.33		i l			
RA		16	2	86	(0.64	0.89					
RA		17	4	86		1.13	1.78					
RA.		18	2	87	(0.50	0.89					
RA		21	1	86).18	0.44					
RA		Totals	21	86	9	9.11	9.33					

· 56


Wolf's Foot VBAR calculations Tree Volume Data From SuperACE VBAR calculated on a per tree basis


Areas 3 & 5

DBH X(quad.)	16.9	Low	High	DBH = ALL
VBAR X	105.8	103.1	108.6	
VBAR CV%	28.3			
VBAR SE%	2.6			
N	118			

Areas 1, 2, 4, & 6

DBH X(quad.)	15.6	Low	High	DBH < 21
VBAR X-	103.7	100.8	106.6	
VBAR CV%	28.51			
VBAR SE%	2.84			*
N	101			







OREGON DEPARTMENT OF FORESTRY WRITTEN PLAN

SALE NAME: Wolf's Foot

LOCATION: Portions of section 13, T1N, R8W, and portions of sections 7, 18, T1N, R7W, W.M., Tillamook

County, Oregon.

ACTIVITIES: Felling and yarding within or adjacent to Type F stream buffers.

PROTECTED RESOURCES:

Streams: Large Type F Stream - Cedar Creek; Medium Type F Streams - Wolf Creek, Arch Cape Mill Creek; Small Type F Stream - Lehman Creek

Riparian Management Area (RMA): The area within 100 feet slope distance from the high water mark on each side of Type F streams.

PROTECTION MEASURES:

YARDING and FELLING:

Streams:

- All trees in the RMA outside of cable corridors are reserved from cutting.
- Trees felled for cable corridors within the RMA will not be removed.
- When cable yarding lines are strung across the RMA they will be pulled out of RMA prior to rigging the next yarding road.
- Adjacent trees will be felled away from or parallel to the RMA.
- If trees or logs fall or slide into a stream channel they will not be limbed, bucked, or removed without approval from State.
- When cable yarding lines are strung across RMA's they will be an average of 150 feet apart and pulled out prior to rigging the next yarding road.
- Ground yarding shall not be allowed within 50 feet of Type F streams

PREPARED BY: Tod Haren

Forester, Central Unit January 28, 2003

OREGON DEPARTMENT OF FORESTRY

WRITTEN PLAN WOLF'S FOOT

Protected Waters:

Wolf Creek, a large type F tributary of the Wilson River, a large type F stream. Two small type F

unnamed tributaries of Cedar Creek, a large type F tributary of the Wilson River.

Location:

Portion of Sections 13, 24, 25, T1N, R8W. W.M. and sections 5, 7, 8, 18, 19, T1N, R7W, W.M.

Tillamook County, Oregon.

Activity:

Road improvement (Widening, cross drain culverts and road rocking) within 100' of a type F stream.

Culvert replacement on two type F streams.

Protection Measures:

No in stream activity will be conducted prior to July 1st or after September 15th without prior approval. Work will only be performed during dry weather periods and low water stream flows. Machine activity in the stream will be kept to a minimum. Water will be diverted around the work area to avoid producing stream sediment. Disturbance of existing vegetation will be kept to a minimum. Fill slopes will be constructed at a 1 ½:1 fill width to height ratio. Rip rap rock will be used to armor the inlet and outlet fill slopes to minimize erosion. Waste material will be end-hauled to stable locations marked in the field. Fill material will be placed and compacted in 8 inch lifts. All disturbed areas will be grass

seeded and fertilized to minimize erosion.

Pipe Geometry:

The culvert replacement at station 2+00 of segment E to F has an existing stream gradient of 7.3 %. A streambed simulation is designed for this location (Option #4). The active channel width was measured at 7.9 feet. Streambed material consists of small cobbles, fine gravel's and sand. A 54' long 103" x 71" aluminized steel arch culvert will be installed at 5.8%. The culvert's outlet invert of the culvert will be placed 1.7 feet below the existing stream gradient. The culvert's inlet invert of the culvert will be placed 2.5 feet below the existing stream gradient. This will result in a cross sectional area at the inlet of 25.1 square feet. The required 50 year peak flow for this drainage is 36 cubic feet per second with a minimum cross sectional area of 9.6 square feet. The site will be monitored to ensure that embedding is achieved. Further information is available in Exhibit "B" of the Wolf's Foot Timber Sale.

The culvert replacement at station 13+00 of segment point E to F has an existing stream gradient of 4.6 %. A streambed simulation is designed for this location (Option #4). The active channel width was measured at 8.5' feet. Streambed material consists of small cobbles, fine gravel's and sand. A 48' long 103" x 71" aluminized steel arch culvert will be installed at 3.1%. The culvert's outlet invert of the culvert will be placed 1.8 feet below the existing stream gradient. The culvert's inlet invert of the culvert will be placed 2.5 feet below the existing stream gradient. This will result in a cross sectional area at the inlet of 25.1 square feet. The required 50 year peak flow for this drainage is 46 cubic feet per second with a minimum cross sectional area of 9.6 square feet. The site will be monitored to ensure that embedding is achieved. Further information is available in Exhibit "B" of the Wolf's Foot Timber Sale.

Prepared by:

Gary Baker Road Specialist

Date: June 3, 2002

\\TILL1NT\PUBLIC\StateForests\Engineers\Timber Sales\Wolfsfoot\WPLAN1.doc

X:\StateForests\CentralUnit\Timber Sale Folders\2002 Sale Plan\Wolfs Foot\Documents\WF_Written Plan.doc