

PART III: EXHIBITS

State Timber Sale Contract
No. 341-05-74
Brown Ridge Corners


EXHIBIT B

Page 1 of 3
629-Form 341-203
Revised 06/97

OREGON DEPARTMENT OF FORESTRY

TIMBER SALE OPERATIONS PLAN

(See Page 2 for instructions)



Date Received by STATE: _____

(5) State Brand Information (complete):

(1) Contract No.: 341-05-74

(2) Sale Name: Brown Ridge Corners

(3) Contract Expiration Date: October 1, 2006

Project Completion Dates: Project No. 3: September 15, 2005

(4) Purchaser: _____

(6) Purchaser Representatives:

Projects: _____

Phone: _____

Cell/Other

Phone: _____

Home: _____

Projects: _____

Phone: _____

Cell/Other

Phone: _____

Home: _____

Projects: _____

Phone: _____

Cell/Other

Phone: _____

Home: _____

Projects: _____

Phone: _____

Cell/Other

Phone: _____

Home: _____

Logging: _____

Phone: _____

Cell/Other

Phone: _____

Home: _____

Logging: _____

Phone: _____

Cell/Other

Phone: _____

Home: _____

Logging: _____

Phone: _____

Cell/Other

Phone: _____

Home: _____

Logging: _____

Phone: _____

Cell/Other

Phone: _____

Home: _____

(7) State Representatives:

Projects: _____

Phone: _____

Cell/Other

Phone: _____

Home: _____

Logging: _____

Phone: _____

Cell/Other

Phone: _____

Home: _____

(8) Name of Subcontractors & Starting Dates:

Projects: No(s) _____ - _____

Date: _____

Phone: _____

Logging: Felling _____

Date: _____

Phone: _____

Yarding: _____

Date: _____

Phone: _____

(9) Comments:

(10) Operations Map: Attach a copy of timber sale Exhibit A or other suitable map which plainly shows the items listed on the instruction sheet.

EXHIBIT B

INSTRUCTION SHEET FOR OPERATIONS PLAN

SUBMIT ONE COPY OF PLAN TO STATE

Operations shall be limited to the work shown in the plan until a revised plan or supplemental plan is submitted covering additional work. Compliance with this plan is not in lieu of compliance with any federal requirements related to the federal Endangered Species Act. If STATE has prepared a required Forest Practices Act (FPA) "Written Plan" for operations, PURCHASER shall comply with all provisions of the Written Plan.

Item No. (from Page 1)

- (5) All sales require you to use a brand furnished by STATE. If the State brand has not been assigned when the plan is submitted, it will be furnished and assigned later. Complete drawing. If more than one brand is assigned to the sale, complete both drawings.
- (6) The contract requires you to have a designated representative available on the sale area or work location who is authorized to receive in your behalf any notice or instruction given by STATE and to take action in regard to performance under the contract. If logging and project work is widely separated, a representative is required for each.
- (7) The STATE representative will be designated when your plan is approved and is the person who will inspect and issue instructions regarding performance.
- (8) Show names of subcontractors to be used for any or all phases of the operations. If subcontractors are not known, or are changed later, give notification to the STATE representative prior to commencement of work by subcontractor.

Show projected dates for commencement of both projects and logging. If projected dates need to be changed at a later date, notification must be given to the STATE representative by supplemental plan or otherwise, prior to commencement of such operations.

- (10) The STATE representative will furnish extra copies of Exhibit A of the contract for your use in preparing the operations map. The map shall use the following legend and show:
 - 1. Landing locations, approximate setting boundaries, and probable sequence of logging the settings. Number the settings in sequence.
 - 2. Locations of spur roads planned for construction, other than those required by the timber sale contract. Provide spur road specifications.
 - 3. Location of proposed tractor yarding roads. Show if and how marked on the ground.
 - 4. Location of temporary stream crossings.
 - 5. List the sequence of performing project work.
 - 6. Location of rock sources - attach pit development plans.




-  Cable landing, with numbers for sequence.
-  Tractor landing with alphabetical sequence.
-  Approximate setting boundary.
-  Spur truck roads.
-  Tractor yarding roads.
-  Temporary stream crossings.

EXHIBIT B
OPERATIONS PLAN


Completion Timeline

Indicate on the appropriate timeline below, the dates by which you plan to complete the work as required under this contract. The purpose of this section is to develop a plan that will ensure you complete the work as required, and meet the interim completion date(s) and contract expiration date. This plan is incorporated and made a part of the contract. When, in the opinion of STATE, operations are not commencing in a manner that meets the intent of this plan, you may be placed in violation of contract and your operations suspended until an amended plan is submitted and approved by STATE.

Projects



Harvest & Other Requirements



The Federal Endangered Species Act (ESA) prohibits a person from taking any federally listed threatened or endangered species. Taking under the federal ESA may include alteration of habitat. STATE's approval of this plan does not certify that PURCHASER's operation under the plan is lawful under the federal ESA. As provided in the timber sale contract, PURCHASERS must comply with all applicable state, federal, and local laws.

PURCHASER's compliance with this plan is not in lieu of compliance with any federal requirements related to the federal Endangered Species Act.

APPROVED: Date: _____

SUBMITTED BY:
PURCHASER

STATE OF OREGON - DEPARTMENT OF FORESTRY

Title _____

Title _____

Original: Salem
cc: District File
Purchaser

EXHIBIT C

SCALING INSTRUCTIONS -- LOCATION APPROVAL -- BRAND INFORMATION

(1) ORIGINAL REGISTRATION Date _____
 REVISION NUMBER _____ Date _____
 CANCELLATION Date _____

(2) TO: _____
 (Third Party Scaling Organization)

(3) FROM: Coos Bay - 07 Phone 541-267-1756
 (State Forestry District)
 Address 63612 Fifth Road Coos Bay, OR 97420

(4) PURCHASER: _____
 Address _____

(12) SALE NAME Brown Ridge Corners

COUNTY Douglas

(13) STATE CONTRACT NUMBER 341-05-74


(14) SCALE: westside eastside cubic foot

(15) STATE BRAND REGISTRATION NUMBER _____

(16) BUREAU BRAND CODE NUMBER _____

(17) STATE BRAND INFORMATION:

(COMPLETE) 



(5) MINIMUM SCALING SPECIFICATIONS			CLASS		
SPECIES	SCALING DIAMETER INCHES	*NET SCALE VOLUME	PER MBF	** SUM	SUB
Conifers	--	10	X		
Hardwoods	--	10	X		

* Apply minimum volume test to whole logs over 40' Westside; 20' Eastside.
 ** Sum (if indicated): see instructions and explain in Item (20).

(6) WESTSIDE SCALE: YES NO
 Actual taper all logs over 40' scaling length

(7) EASTSIDE SCALE: YES NO
 *Actual taper butt logs over 40' scaling length

(8) PENCIL BUCK YES NO
 back to Minimum Scaling Diameter _____

(9) ADD-BACK VOLUME -- YES NO
 Deductions due to delay

(18) PAINT REQUIRED: YES
 COLOR Orange

(19) SPECIAL SCALES PEELABLE CULL (all species) UTILITY/PULP (all species) NO DEDUCTIONS ALLOWED FOR MECHANICAL DAMAGE OTHER: _____ OTHER: _____
--

(10) APPROVED SCALING LOCATIONS	Species	Yard	Truck

(20) REMARKS: Hardwoods may be scaled by the load at 3.5 MBF/Load. Scaler must verify species for each load.

Operator's Name (Optional inclusion by District): _____

(11) NOTICE OF CANCELLATION OF BRAND:
 Effective Date: _____

 State Forester's Representative

(21) SIGNATURES:
 _____ Date
 Purchaser or Authorized Representative
 _____ Date
 State Forester Representative

Notify the District within one hour when branding or painting is inadequate for quick identification, the receipts are missing, not correctly or completely filled out, and/or when logs presented for scaling are impossible to scale accurately.

EXHIBIT C

INSTRUCTIONS FOR FORM 343-307 (rev. 5/01)

- (1) Check appropriate box. REVISION NUMBER requires comments. CANCELLATION requires Item (21). Complete date.
- (2) Designate Third Party Scaling Organization (TPSO). Send 4 copies to TPSO, 1 to purchaser, 1 to Salem, and keep such copies as to district needs.
- (3) State District office, address and phone.
- (4) Enter Purchaser's business name and address as it appears on the Contract.
- (5) Minimum Scaling Specifications. Review Section 2040 or 2045, "Log Removal," of the Contract. Species, or combined species can be separate entries. Information serves as a basis for scaling (see also Items (13) thru (17)), and is required to show existence on the sale. **PerM** (per MBF). **SUM** (lump sum material). **SUB** (submerchantable material. SUB, as used by the State, references that material containing at least 10 bf (net) but less than the lower merchantable net volume limit or grade requirements for other merchantable (PerM) entries. PerM, SUM, and Sub must be indicated by checking the appropriate column. Species with the same specifications and value are combined into one entry. PerM and Sub require scaling therefore complete specifications. SUM need not be scaled, hence no specifications. Loads containing only SUM are to be ticketed if so instructed in Item (19). Mixed loads of SUM, PERM and/or subspecies will always be scaled.
- (6) Westside -- actual taper segment scale. Check Yes or No. Special Service Rules on file with TPSO. See: Segment Scaling and Grading of Long Logs -- All Species -- State Forestry Department Scaling Practices (Westside).
- (7) Eastside -- actual taper/taper table segment scale. Special Service Rules on file with TPSO. See: Segment Scaling and Grading of Long Logs -- All Species -- State Forestry Department Scaling Practices (Eastside). Items with * follow U.S. Forest Service Eastside rules.
- (8) Pencil Buck. Check NO if a westside sale, optional for eastside sales.
- (9) Add-Back Volume. Add-Back is normally checked YES. Scaler records deductions (sap rot, weather checks, etc.) caused by an abnormal delay in removal. Enter separately on scale ticket. TPSO provides State with summaries that include this as a net volume by species. Salvage sales and certain other circumstances may require that "NO" be checked.
- (10) Show scaling locations only applicable to TPSO. Not necessary to list markets. If all species are scaled at same location, enter "ALL."
- (11) When logging is complete, recall branding hammers, date and sign where indicated, check CANCELLATION box at top of form, and send to TPSO.
- (12) Enter sale name and county.
- (13) Enter sale Contract number.
- (14) Check Westside or Eastside log scale. Cubic foot refers to Northwest Log Rules Cubic Foot Scale.
- (15) Oregon Forest Products Brand Registry Number (optional).
- (16) DO NOT USE -- TPSO will fill in when applicable.
- (17) Show one brand only. Complete drawing. If more than one brand is assigned to the sale, (1) make separate form for each brand, and (2) on each form, explain and show other brand(s) under REMARKS, Item 19.
- (18) Check YES and designate orange.
- (19) Special Scales. These are the Special Scales that will be applied. If "Other" is indicated, please describe. Give comments in Item (19).
- (20) Use this space to designate weight conversion factors, or any other explanations to clarify scaling requirements. If additional scaling locations are approved, prepare another form showing all (old and new) locations. Check REVISION box at top of form and explain under remarks. Route as indicated.
- (21) Require purchaser to sign and date completed form.

EXHIBIT D
 FOREST ROAD SPECIFICATIONS

SUBGRADE WIDTH	SURFACED WIDTH	POINT TO POINT	STATION TO STATION	DRAINAGE
14 feet	12 feet	A to B	0+00 to 207+50	Ditch
14 feet	12 feet*	B to C	0+00 to 33+30	Outslope**
14 feet	12 feet*	D to E	0+00 to 9+20	Outslope**
14 feet	12 feet*	F to G	0+00 to 11+25	Outslope**
14 feet	12 feet*	G to H	0+00 to 2+50	Outslope**
14 feet	12 feet*	J to K	0+00 to 3+80	Outslope**
14 feet	12 feet*	K to L	0+00 to 4+00	Outslope**
14 feet	12 feet*	K to M	0+00 to 13+80	Outslope**
14 feet	12 feet*	N to O	0+00 to 5+80	Outslope**
14 feet	12 feet*	P to R	0+00 to 22+35	Outslope**

*Surfaced width only applies if "WINTER AND WET WEATHER OPTION" is chosen.

**Drainage shall be changed to Ditch if "WINTER AND WET WEATHER OPTION" is chosen.

CLEARING. This work shall consist of clearing, removing, and disposing of all trees, Snags, Down Timber, brush, surface objects, and protruding obstructions within the clearing limits.

Where clearing limits have not been marked, the "Road Brushing Specifications" in Exhibit D shall apply. Clearing debris shall not be placed or permitted to remain in or under any road embankment sections. Clearing debris shall not be left lodged against standing trees.

All danger trees, leaners, and Snags outside the clearing limits which could fall and hit the road shall be felled.

GRUBBING. This work shall consist of the removal or digging out of stumps and protruding objects.

All stumps shall be completely removed within the limits of required grubbing. Stumps overhanging cutslopes shall be removed. Grubbing debris shall not be placed or permitted to remain in or under any road embankment sections. Grubbing debris shall not be left lodged against standing trees. Grubbing classifications are as follows:

New construction - From the top of the cutslope to the toe of the fill.

Improvements and reconstructions - 4 feet back from the shoulder of the subgrade or ditch, whichever is widest, or as marked in the field.

CLEARING AND GRUBBING DISPOSAL. Scatter through openings in the timber outside of the cleared right-of-way, except areas where end-haul is required.

EXHIBIT D
FOREST ROAD SPECIFICATIONS

EXCAVATION. Excavation and grading shall not be done when weather and/or ground conditions are such that damage will result to existing subgrade or cause excessive erosion.

Excavation shall conform to STATE-engineered lines, grades, dimensions, and plans when provided.

All suitable excavated material shall be used where possible for the formation of fills, shoulders, and drainage structure backfills. Embankment materials shall be free of woody debris, brush, muck, sod, frozen material, and other deleterious materials. All fills and drainage structure backfills shall be machine compacted according to the specifications in Exhibit F.

Unless road design plans show otherwise, all roads shall be on a balanced cross section, except when the slope is over 50 percent, the road shall be on full bench for the width specified.

Excess excavation shall not be sidecast where material will enter a stream course or where material will accumulate in areas deemed a high landslide hazard location by STATE.

ROAD WIDTH LIMITATIONS. PURCHASER shall obtain advance written approval from STATE to construct the road to a greater width than specified. Extra subgrade width shall be required for:

Fill Widening. Add to each fill shoulder 1 foot for fills 3 feet to 6 feet high; 2 feet for fills over 6 feet high.

Curve Widening. Widen the inside shoulder of all curves as follows: 400 divided by the radius of the curve equals the amount of extra width.

DRAINAGE

Ditch. Construct "V" ditch 3 feet wide and to a depth of 1 foot below subgrade. Subgrade shall be crowned at 4 to 6 percent. Construct ditchouts away from subgrade at locations marked in the field.

Outslope. Road subgrade shall be outsloped at 4 to 6 percent.

TURNOUTS. Increase roadbed width an additional 8 feet for both subgrade and surfacing. Length shall be at least 25 feet, or as staked on the ground, plus 25-foot approaches at each end.

Location: As marked in the field.

GRADING

	<u>Back Slopes</u>	<u>Fill Slopes</u>
Rock	Vertical to 1/4:1	Not steeper than 1½:1
Common - side slopes 50% and over	3/4:1	
Common - side slopes less than 50%	1/2:1	
Common - turnpike (level) section	2:1	

Top of cutslope shall be rounded.

LANDINGS. Landings shall be constructed as Directed by STATE. Surface is to be crowned for drainage, with general grade no more than 3 percent.

EXHIBIT D


ADDITIONAL ROAD IMPROVEMENT/CONSTRUCTION INSTRUCTIONS

- A to B – This road shall be bladed in order to achieve a smooth running surface.
- B to C – The brush and small trees shall be removed from the road prism and scattered outside of the road edges. Cutbank slough can generally be spread out within the existing road prism. Excessive slide material and material from road widening shall be removed and hauled to waste areas along the road, as shown on Exhibit A. The road surface shall be bladed.
- C – A landing shall be constructed at this point. The brush and stumps shall be removed and material excavated to construct the landing floor.
- D to E – This is a road to be constructed. No end-hauling of waste material will be necessary.
- F to G – A cat shall be used to widen the road at STA 8+75. This material shall be wasted in the existing road prism. The cutbank slough shall also be distributed in the road prism. The road surface shall be bladed.
- G to H – This is a road to be constructed. No end-hauling of waste material will be necessary.
- J to K – A small portion of this road (100') shall be widened. The majority of material shall be hauled to the waste areas as shown on Exhibit A. The cutbank slough and slide material shall be drifted and spread within the road prism just past the widening portion and towards Point K. The road surface shall be bladed. Note that 300 to 400 cubic yards of material can be disposed of at Point J.
- K to L – This is a road to be constructed. No end-hauling of waste material will be necessary.
- K to M – This is a road to be constructed. Any excess material shall be hauled to the waste areas shown on Exhibit A.
- N to O – This road shall be opened by removing the brush and small trees. The road surface shall be bladed. Note that Point N is a suitable location for waste material if needed.
- P to R – This road shall be opened by removing the waterbars. The road surface shall be bladed.
- Q – The landing at this location shall be cleared of brush and small trees and the surface smoothed.
- S – Install a 78" x 60' 12 gage aluminized culvert (see written plan and site plans for details). This culvert will be countersunk 31.2 inches below the finished stream gradient. Excess material and material not suitable to be reused to fill over the pipe shall be hauled to a waste area as shown on the attached Exhibit A.

ADDITIONAL ROAD IMPROVEMENT/CONSTRUCTION INSTRUCTIONS
(WINTER AND WET WEATHER OPTION ONLY)

B to C, D to E, F to G, G to H, J to K, K to L, K to M, N to O, P to R – Ditches shall be added for drainage. Culverts shall be replaced or installed as required in locations As Directed by STATE. Road surface shall be prepared for rock surfacing.

EXHIBIT D
ROAD BRUSHING SPECIFICATIONS



REQUIREMENTS

Unless otherwise approved in writing by STATE, brush and trees shall be cut to a height of 6 inches or less above the ground surface or obstructions such as rocks or existing stumps.

PURCHASER is required to **either** clear up to the designated clearing height as shown on the above diagram **or** clear the designated distance past the top of the cutbank as shown on the above diagram.

Debris resulting from the brushing operation shall be removed from the roadway, cutslope, ditches, and water courses within 72 hours and may be scattered downslope from the road or placed in other stable locations, unless otherwise approved by STATE.

EXHIBIT D
END-HAULING REQUIREMENTS

POINT TO POINT	STA. TO STA.	WASTE AREA LOCATION	WASTE AREA TREATMENT
B to C	0+00 to 33+30	(1)	(1, 2, 3)
J to K	0+00 to 3+80	(2)	(1, 2, 3)

End-Haul Areas General Requirements

Material shall not be intentionally side cast.

Clearing and grubbing debris shall be end-hauled.

When blasting is required, it shall be accomplished using timing devices, delayed charges, low intensity shots, or other suitable means to contain as much material as possible within the road prism.

Containment

Full containment: The amount of material lost over the outside edge of the road shall not exceed 6 inches in depth measured perpendicular to the natural ground slope. Pioneer excavation shall be removed by digging, loading, and hauling rather than by pushing or scraping methods.

Trees and stumps may have up to 12 inches of material directly above them. Any amount of material exceeding the containment requirements shall be removed by whatever means necessary and end-hauled to a designated waste area.

Waste Area Location

- (1) Various waste areas along road between Points B to C.
- (2) Waste area near Point J and as shown on Exhibit A.

Waste Area Treatment

- (1) Deposit at waste area, spread evenly, compact, and provide adequate drainage.
- (2) Pile woody debris separate from other waste material.
- (3) See Exhibit D – Special Instruction for Road Improvement/Construction.

EXHIBIT E
 ROAD SURFACING

TYPE OF ROCK	SIZE OF ROCK	Description	Location	APPROX. TOTAL TRUCK MEASURE VOLUME	
Scalps	Less than ¾"	Bedding for culvert	1900 Rd. Point S	287.28 Ton	216 CY
Hard Crushed Quarry	2½"-0"	Base for 1900 Road after culvert installation	1900 Rd. Point S	95.76 Ton	72 CY
Hard Crushed Quarry	1½"-0"	Surface rock for 1900 Rd after culvert installation	1900 Rd Point S	71.82 Ton	54 CY
Rip Rap	12"-24"	Rip Rap for culvert installation	1900 Rd Point S	39.9 Ton	30 CY

ROAD SURFACING
 (WINTER AND WET WEATHER OPTION ONLY)

TYPE OF ROCK	SIZE OF ROCK	COMP. DEPTH	YDS/ STA	TONS/ STA	POINT TO POINT	STATION TO STATION	APPROX. TOTAL TRUCK MEASURE VOLUME	
Hard Crushed Quarry	1½"-0"	3" (uncomp)	11.5	15.24	A to B	0+00 to 207+50	3184.02 Ton	2394 CY
Hard Crushed Quarry	2½"-0"	8"	48.1	64.04	B to C	0+00 to 33+30	2160.66 Ton	1602 CY
Hard Crushed Quarry	2½"-0"	8"	48.1	64.04	D to E	0+00 to 9+20	598.50 Ton	450 CY
Hard Crushed Quarry	2½"-0"	8"	48.1	64.04	F to G	0+00 to 11+25	718.20 Ton	540 CY
Hard Crushed Quarry	2½"-0"	8"	48.1	64.04	G to H	0+00 to 2+50	167.58 Ton	126 CY
Hard Crushed Quarry	2½"-0"	8"	48.1	64.04	J to K	0+00 to 3+80	239.40 Ton	180 CY
Hard Crushed Quarry	2½"-0"	8"	48.1	64.04	K to L	0+00 to 4+00	263.34 Ton	198 CY
Hard Crushed Quarry	2½"-0"	8"	48.1	64.05	K to M	0+00 to 13+80	885.78 Ton	666 CY
Hard Crushed Quarry	2½"-0"	8"	48.1	64.04	N to O	0+00 to 5+80	383.04 Ton	288 CY
Hard Crushed Quarry	2½"-0"	8"	48.1	64.04	P to R	0+00 to 22+35	1436.40 Ton	1080 CY
LANDINGS	SIZE OF ROCK	COMP. DEPTH	YDS/ LND	TONS/ LND	NO. OF LNDGS.	POINTS	APPROX. TOTAL TRUCK MEASURE VOLUME	
Hard Crushed Quarry	6" Jaw Run	6"	54	71.82	6	E, H, L, M, O, Q	430.92 Ton	324 CY

Roads shall be uniformly graded and approved by STATE prior to rocking

PURCHASER may substitute a non-spec base rock for a portion of the 2½"-0" rock in the "WINTER AND WET WEATHER OPTION", as approved in writing by STATE.

EXHIBIT E CRUSHED ROCK SPECIFICATIONS

Materials. The material shall be fragments of rock or other hard, durable particles crushed to the required size and a filler of finely crushed stone, sand, or other finely divided mineral matter. The material shall be free from vegetation and lumps of clay.

Quality and Grading Requirements. The stone base materials shall be crushed rock, including sand. River gravel shall not be used.

The material from which base material is produced or manufactured shall meet the following test requirements:

Hardness - Test Method AASHTO T 96 35% Maximum

Durability - Test Method ODOT TM 208
Passing No. 20 Sieve: 30% Maximum
Sediment Height: 6" Maximum

<u>For 1½"-0"</u>	Passing	2" sieve	100%
	Passing	1½" sieve	95-100%
	Passing	¾" sieve	55-75%
	Passing	¼" sieve	35-50%

Of the fraction passing ¼" sieve, 40% to 60% shall pass the No. 10 sieve.

<u>For 2½" -0"</u>	Passing	3" sieve	100%
	Passing	2½" sieve	95-100%
	Passing	1¼" sieve	55-75%
	Passing	¼" sieve	30-45%

Of the fraction passing ¼" sieve, 40% to 60% shall pass the No. 10 sieve.

<u>For Jaw-Run</u>	Passing	6" sieve	100%
	Passing	3" sieve	45-65%

For Scalps

- (1) Consisting of all non-organic material.
- (2) Less than ¾" in size.

For 12" – 24" Riprap 50 percent of the material shall measure at least 24 inches in one dimension. Material shall be clean, well graded, and free of 2" – 0" fines.

EXHIBIT E

ROCK ACCOUNTABILITY

The rock shall meet the quality and size specifications in Exhibit E. A sample of the rock shall be supplied to STATE for testing and approval prior to rocking. PURCHASER shall obtain subgrade approval from STATE prior to rocking. Rocking shall be limited to periods when weather conditions are acceptable to STATE and when sediments will not enter streams.

Rock accountability shall be determined by the following methods, as directed by STATE. STATE shall be given 24 hours' notice prior to rocking.

Load Records. Notify STATE before spreading the rock and maintain a record of all rock delivered for spreading. Make the record available for STATE inspection. A report listing the amount of rock delivered the prior month must be submitted no later than the 15th of each month.

EXHIBIT F

COMPACTION AND PROCESSING REQUIREMENTS

Subgrade. Subgrade surfaces of the road segments listed below shall be graded and compacted prior to rocking. Compaction shall be accomplished by traveling all surfaces from shoulder to shoulder until visible deformation ceases, or in the case of a sheepsfoot roller, the roller "walks out." At least 3 passes shall be made over the entire width and length of the road. A pass is defined as traveling a road section in one direction and then back over that same section again. Compaction shall be accomplished by using the approved equipment listed below or others approved by STATE:

Subgrade shall be crowned at 4 to 6 percent unless otherwise specified.

ROAD SEGMENT	COMPACTION EQUIPMENT OPTIONS
B to C*, D to E*, F to G*, G to H*, J to K*, K to L*, K to M*, N to O*, P to R*	Vibratory Roller

*Only required if "WINTER AND WET WEATHER OPTION" is chosen.

Fills. Embankments and fills shall be placed in (approximately) horizontal layers not more than 8 inches in depth. Each layer shall be separately, and thoroughly, compacted. Compaction equipment shall be operated over the entire width of each layer until visible deformation of the layers ceases or, in the case of a sheepsfoot roller, the roller "walks out." At least 3 passes shall be made over the entire width and length of each layer. A pass is defined as traveling a fill layer in one direction and then back over that same layer again.

Placing individual rocks or boulders with more depth than the allowed layer thickness shall be permitted, provided the embankment will accommodate them. Such rocks and boulders shall be at least 6 inches below the subgrade. They shall be carefully distributed and the voids filled with finer material, forming a dense and compacted mass. Compaction shall be accomplished by using the approved equipment listed below or others approved by STATE:

ROAD SEGMENT	COMPACTION EQUIPMENT OPTIONS
D to E, G to H, K to L, K to M	Crawler Tractor

EXHIBIT F

COMPACTION AND PROCESSING REQUIREMENTS

Crushed Rock. The rock shall be uniformly mixed and spread in layers on the approved roadbed. Each layer of crushed rock shall be moistened or dried to a uniform moisture content suitable for maximum compaction and compacted in layers not to exceed 6 inches in depth. When more than 1 layer is required, each shall be shaped and compacted before the succeeding layer is placed. Any irregularities or depressions that develop during compaction of the top layer shall be corrected by loosening the material at these places and adding or removing material until the surface is smooth and uniform. Each layer shall be compacted with a minimum of 3 passes over the entire width and length of the road. A pass is defined as traveling a road section in one direction and then back over that same section again. Compaction shall be accomplished by using the approved equipment listed below or others approved by STATE:

Rock shall be compacted and processed during the same project period it is spread, unless otherwise approved in writing by STATE.

Rock shall be crowned at 4 to 6 percent unless otherwise specified.

ROAD SEGMENT	COMPACTION EQUIPMENT OPTIONS
B to C*, D to E*, F to G*, G to H*, J to K*, K to L*, K to M*, N to O*, P to R*	Vibratory Roller

*Only required if "WINTER AND WET WEATHER OPTION" is chosen.

COMPACTION EQUIPMENT OPTIONS

Vibratory Rollers. The drum shall have a smooth surface, a diameter not less than 48 inches, a width not less than 58 inches, and a turning radius of 15 feet or less. Vibration frequency shall be regulated in steps to 1400, 1500, and 1600 VPM, corresponding to engine speeds of 1575, 1690, and 1800 RPM. The centrifugal force developed shall be 7 tons at 1600 VPM. It shall be activated by a power unit of not less than 25 horsepower. The vibratory roller shall be self-propelled and operated at speeds ranging from 0.9 miles to 1.8 miles per hour, as directed by STATE.

Crawler Tractors. D-7 Caterpillar or equivalent or larger.

EXHIBIT G
CULVERT SPECIFICATIONS

All culvert materials shall be furnished and installed by PURCHASER, unless otherwise specified in the Contract. Culverts shall be constructed of corrugated galvanized or aluminized steel. Corrugated polyethylene may be used for sizes up to 36 inches in diameter. All culverts shall conform to the material and fabricating requirements of the "Standard Specifications for Highway Construction" prepared by the Highway Division of the Oregon State Department of Transportation. Corrugation types and shapes other than those meeting the above minimum Highway requirements, shall be approved in writing by STATE.

Culverts shall be located according to the alignment and grade as shown on the Plan and Profile, and/or as staked in the field, or as stipulated in special instructions.

The STATE Representative shall determine final culvert locations and stake the locations in the field prior to installation.

Culvert grade shall slope away from ditch grade at least 2 percent unless otherwise specified.

Culverts less than 36 inches in diameter shall be installed with the lock seam on the inlet end placed within 45 degrees of the bottom of the trench.

The foundation and trench walls for all culverts shall be free from logs, stumps, limbs, stones, and other objects which would dent or damage the pipe. The culvert trench shall be excavated 3 pipe diameters wide to Permit compaction and working on each side of the pipe. Tamping shall be done in 6-inch lifts, 1 pipe diameter each side of the pipe to 95 percent density or over. Bedrock shall be excavated as required to provide a uniform foundation for the full length of the culvert.

A bedding of granulated material or crushed rock as specified shall be placed to provide a wide band of support and to transmit the load from above evenly over the entire length of the pipe.

Backfill shall consist of granulated material, crushed rock, or job-excavated soil free of stumps, limbs, rocks, or other objects which would damage the pipe.

Transporting of the pipe shall be done carefully. Dragging or allowing free fall from trucks or into trenches shall not be permitted.

Joining shall be done with bands of like material and corrugations. Manufacturers' instructions shall be followed for prefabricated pipe assembly.

Polyethylene joints shall be made with split couplings, corrugated to engage the pipe corrugations, and shall engage a minimum of 4 corrugations, 2 on each side of the pipe joint.

A manufacturer's certification that the product was manufactured, tested, and supplied in accordance with this specification shall be furnished to the Project Engineer upon request.

EXHIBIT G
 CULVERT SPECIFICATIONS

Minimum height of cover over top of culvert to subgrade when road is to be rocked shall be as follows: 12" for culverts 18" to 36" and 18" for culverts 42" to 96" (add 6" for roads which will not be rocked). Minimum vertical cover for other designs shall be as specified by STATE.

Lengths of individual culvert sections shall be not less than 10 feet, unless otherwise provided for in special instructions.

The ends of each culvert shall be free of logs and debris which would restrict the free flow of water. The intake end of relief culverts shall be provided with a sediment catching basin 3 feet in diameter at the bottom. The outlet end of any culvert which would allow water to erode embankment soil shall be provided with a half round or other approved slope protection device. Construct lead-off ditches away from culvert outlets where the slope gradients restrict the free flow of water.

Following are the minimum standard gauges for pipe and coupling bands. Some culverts may require different gauges and may be found in the culvert listing.

Dia.	Steel Pipe Gauge	Band Gauges	Band Widths (")			Hugger Band Widths (")	
			Annular	Helical	Dimpled	Annular	Helical
12-15	16	16	7	12	12	13 1/8	10 1/2
18-24	16	16	12	12	12	13 1/8	10 1/2
30-36	16	16	12	12	12	13 1/8	10 1/2
42	14	16	12	12	NA	13 1/8	10 1/2
48	14	16	24	24	NA	13 1/8	10 1/2
54	14	16	24	24	NA	13 1/8	10 1/2
60	12	16	24	24	NA	13 1/8	10 1/2
66-72	12	16	24	24	NA	13 1/8	10 1/2
78	12	16	24	24	NA	13 1/8	10 1/2
84	12	16	24	24	NA	14 3/4	10 1/2
90-120	12	16	26	26	NA	NA	NA

Culverts larger than 60" in diameter shall have 3" x 1" corrugations.

Polyethylene culverts shall be double walled and meet the requirements of AASHTO M-294-901, Type S.



EXHIBIT G
 CULVERT LIST

CULVERT NO.	DIAMETER (Inches)	LENGTH (Feet)	POINT	STATION
1	78	60	Point S	--

CULVERT LIST
 (WINTER WET WEATHER OPTION ONLY)


CULVERT NO.	DIAMETER (Inches)	LENGTH (Feet)	ROAD SEGMENT POINT TO POINT	STATION
2	18	30	B to C	As Directed
3	18	30	B to C	As Directed
4	18	30	B to C	As Directed
5	18	40	B to C	As Directed
6	18	30	D to E	As Directed
7	18	30	F to G	As Directed
8	18	30	J to K	As Directed
9	18	30	K to M	As Directed
10	18	30	K to M	As Directed
11	18	30	N to O	As Directed

EXHIBIT H
 WATERBAR SPECIFICATIONS



SPACING OF WATERBARS

ROAD GRADE	DISTANCE
≤ 5%	300'
6-10%	200'
11-15%	100'
16-20% or greater	50'



**WATERBAR SPECIFICATIONS
 FOR CROSS DITCHING #298**

PART IV: OTHER INFORMATION

State Timber Sale Contract
No. 341-05-74
Brown Ridge Corners

Page 1 of 2

WRITTEN PLAN

Timber Sale Name: Brown Ridge Corners
Project Name: Bickford Creek culvert replacement
Legal: SE ¼ SW ¼ of Section 23, T.23S., R.10W., W.M., Douglas County, Oregon
Landowner: Oregon Department of Forestry
Landowner Address: 63612 Fifth Rd
Coos Bay, OR. 97420
Landowner Telephone Number: (541) 267-4136
Notification Number: _____
Written Plan Submitted By: James McIntosh
Engineering Unit Supervisor

PROTECTED RESOURCE:

- Bickford Creek

SITUATION:

- The existing culvert was originally installed at this site about 25 years ago. The pipe is undersized based on the amount of acres that drain into the area above the pipe inlet. Elliott State Forest road No. 1900 crosses over this pipe and provides access to approximately 480 acres of State Forest Land located beyond this crossing. The bottom portion of the pipe exhibited signs of excessive age related deterioration. The pipe was removed during the month of August, 2004, in order to circumvent any risk of the road fill from washing out during the up and coming winter months. Also, the existing pipe had a 3 foot drop at the outlet which created a barrier to fish.

STREAM CHARACTERISTICS:

- Bickford Creek is a medium Type "F" stream with an average gradient of 3%.
- The stream gradient upstream and downstream of the culvert was measured using a Leica Total Station and prism pole, beyond the influence of the existing culvert.
- The active channel width was estimated to be 6½ feet.
- The streambed below the existing culvert is comprised of small to large cobble. Above the culvert, the streambed consists of fine material that collected above the inlet. Note that the area above the pipe inlet was originally designed to be a pond. The pond was completely filled in with material that migrated downstream during the 1996 storm event.
- The bed material appears deep enough to countersink the culvert. Since the crossing is in an area with deep valley fill material.

INSTALLATION PLAN:

- ❑ The existing culvert has already been removed and is setting near the site. It will be disposed of in an approved disposal site.
- ❑ The stream channel will be re-router through an overflow culvert during installation.
- ❑ A sediment trap will be utilized to prevent sediment from flowing downstream.
- ❑ Excess material removed from the fill will be placed in a disposal site as shown on the attached map.
- ❑ Backfill material will be placed in one-foot lifts and machine compacted across the entire width of the fill.
- ❑ All work will be done during the in water work period between July 1 and September 15 unless approval is granted by ODFW to begin work at an earlier date.
- ❑ All exposed soil will be seeded immediately after construction

PIPE INSTALLATION:

- ❑ Streambed simulation strategy will be used. (Counter sink culvert evenly)
- ❑ A 60-foot long, 78-inch diameter (12 Gage) round pipe will be placed in the crossing.
- ❑ The pipe will be placed on a 3% gradient.
- ❑ The bottom of the pipe will be placed 31.2 inches below the natural channel elevation at the inlet and the outlet (31.2 inches = 40% of pipe diameter).
- ❑ The streambed elevations below the old culvert were used as control to determine the depth of sinking the new culvert.
- ❑ The culvert will not be manually filled allowing the natural migration of existing material within the streambed to move downstream and into the culvert. The result of this process will equalize the stream gradient above the culvert inlet to that below the outlet.
- ❑ Watershed area equals approximately 430 acres or 0.67 square miles.
- ❑ 50-year event using ODF methodology: 200 cfs per square mile.
- ❑ Estimated 50-year flow at the crossing: 134 cfs (.67 x 200).
- ❑ Culvert capacity: 78" pipes maximum flow = 220 cfs.
- ❑ 37 percent loss in capacity because of being countersunk: (0.63 x 220 = 138.6 cfs)
- ❑ Effective capacity: 138.6 cfs (greater than 50-year peak flow).
- ❑ Rip-rap material shall be placed around the culvert inlet area to protect the fill and at function as an inlet control device.

O.D.F. Representative Date

Purchaser Representative Date

Operator Representative Date

APPROVED BY: _____ Date: _____