# PART III: EXHIBITS

State Timber Sale Contract No. 341-17-55 Livin' on a Prayer

# **EXHIBIT B**

Page 1 of 3 629-Form 341-203 Revised 06/97

## OREGON DEPARTMENT OF FORESTRY

## TIMBER SALE OPERATIONS PLAN

(See Page 2 for instructions)

Date	Received by STATE:	(5) State Brand	Information (complete):	$\sim$
(1)	Contract No.: 341-17-55	<u> </u>	(	
(2)	Sale Name: Livin' on a Prayer	<u></u>		-
(3)	Contract Expiration Date: October 31, 2018	Project Completio	on Dates:	
(4)	Purchaser:			
` ′	Purchaser Representatives:			
(6)	r urchaser Representatives.		Cell/Other	
	Projects:	Phone:		Home:
	n .		Cell/Other	
	Projects:	Phone:	Phone: Cell/Other	Home:
	Projects:	Phone:		Home:
	110,000.		Cell/Other	
	Projects:	Phone:		Home:
			Cell/Other	
	Logging:	Phone:		Home:
	Logging	Phone:	Cell/Other Phone:	Home:
	Logging:	Filone	Cell/Other	_ nome.
	Logging:	Phone:		Home:
	-66 6		Cell/Other	<u>-</u>
	Logging:	Phone:	Phone:	Home:
(7)	State Representatives:			
(,,	State Hepresonau (es)		Cell/Other	
	Projects:	Phone:	Phone:	Home:
			Cell/Other	
	Logging:	Phone:	Phone:	Home:
(8)	Name of Subcontractors & Starting Dates:			
	Projects: No(s)	Date:	Phone:	
(7)	No(s)	Date:	Phone:	
	No(s)	Date:	Phone:	
	No(s)	Date:	Phone:	
	Logging: Felling	Date:	Phone:	
	Yarding:	Date:	Phone:	
(9)	Comments:			

(10) Operations Map: Attach a copy of timber sale Exhibit A or other suitable map which plainly shows the items listed on the instruction sheet.

#### **EXHIBIT B**

#### INSTRUCTION SHEET FOR OPERATIONS PLAN

#### SUBMIT ONE COPY OF PLAN TO STATE

Operations shall be limited to the work shown in the plan until a revised plan or supplemental plan is submitted covering additional work. Compliance with this plan is not in lieu of compliance with any federal requirements related to the federal Endangered Species Act. If STATE has prepared a required Forest Practices Act (FPA) "Written Plan" for operations, PURCHASER shall comply with all provisions of the Written Plan.

#### **Explanation of Item No. (from Page 1)**

- (5) All sales require you to use a brand furnished by STATE. If the State brand has not been assigned when the plan is submitted, it will be furnished and assigned later. Complete drawing. If more than one brand is assigned to the sale, complete both drawings.
- (6) The contract requires you to have a designated representative available on the sale area or work location who is authorized to receive in your behalf any notice or instruction given by STATE and to take action in regard to performance under the contract. If logging and project work is widely separated, a representative is required for each.
- (7) The STATE representative will be designated when your plan is approved and is the person who will inspect and issue instructions regarding performance.
- (8) Show names of subcontractors to be used for any or all phases of the operations. If subcontractors are not known, or are changed later, give notification to the STATE representative prior to commencement of work by subcontractor.
  - Show projected dates for commencement of both projects and logging. If projected dates need to be changed at a later date, notification must be given to the STATE representative by supplemental plan or otherwise, prior to commencement of such operations.
- (10) The STATE representative will furnish extra copies of Exhibit A of the contract for your use in preparing the operations map. The map shall use the following legend and show:
  - 1. Landing locations, approximate setting boundaries, and probable sequence of logging the settings. Number the settings in sequence.
  - 2. Locations of spur roads planned for construction, other than those required by the timber sale contract. Provide spur road specifications.
  - 3. Location of proposed tractor yarding roads. Show if and how marked on the ground.
  - 4. Location of temporary stream crossings.
  - 5. List the sequence of performing project work.
  - 6. Location of rock sources attach pit development plans.

1	Cable Landing, with numbers for sequence.				
A	Tractor Landing with alphabetical sequence.				
	Approximate setting boundary.				
	Spur truck roads.				
	Tractor yarding roads.				
X	Temporary stream crossings.				

#### **EXHIBIT B**

#### **OPERATIONS PLAN**

#### **Completion Timeline**

Indicate on the appropriate timeline below, the dates by which you plan to complete the work as required under this contract. The purpose of this section is to develop a plan that will ensure you complete the work as required, and meet the interim completion date(s) and contract expiration date. This plan is incorporated and made a part of the contract. When, in the opinion of STATE, operations are not commencing in a manner that meets the intent of this plan, you may be placed in violation of contract and your operations suspended until an amended plan is submitted and approved by STATE.

#### **Projects**



#### **Harvest & Other Requirements**



The Federal Endangered Species Act (ESA) prohibits a person from taking any federally listed threatened or endangered species. Taking under the federal ESA may include alteration of habitat. STATE's approval of this plan does not certify that PURCHASER's operation under the plan is lawful under the federal ESA. As provided in the timber sale contract, PURCHASERS must comply with all applicable state, federal, and local laws.

PURCHASER's compliance with this plan is not in lieu of compliance with any federal requirements related to the federal Endangered Species Act.

	ED: Date: F OREGON - DEPARTMENT OF FORESTRY	SUBMITTED BY: PURCHASER	
Title _		Title	
Original: cc:	Salem District File Unit		

Operator
(Purchaser Representative)\_\_\_\_\_

Purchaser

State Timber Sale Contract No. 341-17-55 Livin' on a Prayer Page 1 of 2 629-Form 343-307a Revised 11/11

# EXHIBIT C – SAWMILL GRADE (EASTSIDE SCALE) SCALING INSTRUCTIONS -- LOCATION APPROVAL -- BRAND INFORMATION

(1)		REGISTRATION NUMBER ATION	☐ Da	te te te		_	(9) (10)	SALE NAME: Livin' on a Prayer  COUNTY: Klamath  STATE CONTRACT NUMBER: 341-17-55
(2)	TO:	(Third Party Scaling	g Organiza	ition)		_	(11)	STATE BRAND REGISTRATION NUMBER:
(3)	(Si	,	(10) Phone <u>541-883-5681</u>			<u>l</u>	(12)	STATE BRAND INFORMATION (COMPLETE):
(4)	PURCHAS Mailing Add	ER:dress:				_		
(5)	MININ	IUM SCALING SPE  SCALING DIAMETER		TIONS		-		
	SPECIES Conifers Hardwoods	INCHES		10 10	ME		(13)	PAINT REQUIRED: YES 🗵 COLOR: Orange
(6)	EASTSIDE Use Region 6 actu Weight Sca	al taper rule. Logs over 40'.		YES	NO		NC ME PE	EELABLE CULL (all species)
(8)	LOCATI	VED SCALING ONS pproved Locations web-site)	Species	Yard	Truck	Weight		REMARKS
							_	
							-	tor's Name (Optional inclusion by District):
							(10)	SIGNATURES:
								Purchaser or Authorized Representative Date
								State Forester Representative Date
								State Forester Representative PRINT NAME

Notify the District within one hour when branding or painting is inadequate for quick identification, the receipts are missing, not correctly or completely filled out, and/or when logs presented for scaling are impossible to scale accurately.

# **EXHIBIT C – SAWMILL GRADE**INSTRUCTIONS FOR FORM 343-307a (rev. 11/11)

(1) Check appropriate box. REVISION NUMBER requires comments. CANCELLATION requires logging and hauling to be complete, recall branding hammers, date and sign where indicated, write diagonally across page "CANCEL", and send to TPSO.

(2) Designate Third Party Scaling Organization (TPSO).

Columbia River Log Scaling & Grading Bureau

P.O. Box 7002, Eugene, OR 97401

Phone: (541) 342-6007 Fax: (541) 342-2631

Email: services@crls.com

Mountain Western Log Scaling & Grading Bureau

P.O. Box 580, Roseburg, OR 97470

Phone: (541) 673-5571 Fax: (541) 672-6381

Email: info@mwlsqb.com

Northwest Log Scalers, Inc

5526 NE 122<sup>nd</sup> Ave, Portland, OR 97230

Phone: (503) 254-0600 Fax: (503) 408-0919

Email: info@nwlogscalers.com

Pacific Rim Log Scaling Bureau, Inc.

8288 28<sup>th</sup> Court North East, Lacey, WA 98516 Phone: (360) 528-8710 Fax: (360) 528-8718

Email: office@prlsb.com

Yamhill Log Scaling & Grading Bureau P.O. Box 709, Forest Grove, OR 97116

Phone: (503) 359-4474 Fax: (503) 359-4476

Email: yamhill@attglobal.net

Pacific Log Scaling & Grading Bureau, Inc. P.O. Box 23939, Portland, OR 97281

Phone: (503) 684-5599 Fax: (503) 639-4880

Email: PacLogScale@aol.com

- (3) State District office, address and phone.
- (4) Enter Purchaser's business name, address, and phone number as it appears on the Contract.
- (5) Minimum Scaling Specifications. Scaling diameter inches is used for pencil buck minimum diameter.
- (6) Eastside Region 6 actual taper/taper table segment scale. Check Yes or No. Special Service Rules on file with TPSO. See: Segment Scaling and Grading of Long Logs -- All Species -- State Forestry Department Scaling Practices (Northwest Log Rules Eastside). Items with \* follow U.S. Forest Service Eastside rules.
- (7) Weight Scale Sample Check box if sale is to be a Weight Scale Sample. All specifics for handling, scaling and processing will be attached or explained in the Remarks section Item (15).
- (8) Show scaling locations only applicable to TPSO. Location name should appear as it does on the ODF Approved Scaling Location web site: http://www.odf.state.or.us/DIVISIONS/management/asset\_management/ScalingLocation.asp Locations with scaling and processing directions specific to their location should be on a separate form. Species should be identified if not capable of receiving "all" species. Check appropriate box for either: yard, truck scale, or weight. Refer to the web site listed above for the locations approval status.
- (9) Enter sale name and county.
- (10) Enter sale Contract number.
- (11) Enter Oregon's State Brand Registry Number (REQUIRED).
- (12) Show brand assigned to timber sale. One brand only. If more than one brand is assigned to the sale: (1) make a separate form for each brand and (2) on each form, explain and show other brand(s) in the Remarks section Item (15).
- (13) Check yes for Paint Required and designate "Orange" for color. Non required removal volumes may sometimes require blue paint.
- (14) Special Requests. These are requests that will be applied to ODF timber sales. All boxes applicable to the timber sales designated in the Exhibit C form must be "marked". If "Other" is indicated, it must contain a description and any necessary comments.
- (15) Use this space to designate any weight conversion factors, per load volumes, weight scale sample instructions or any other explanations to clarify scaling, processing and/or mailing requirements. If additional scaling locations are approved, revise original or current form showing all (old and new) locations. Check REVISION box at top of form and explain under remarks. Route as indicated.
- (16) Require purchaser to sign and date completed form in addition to State Forester Representative, sign and print name on the form.

#### **EXHIBIT D**

#### FOREST ROAD SPECIFICATIONS

#### CONSTRUCTION

SUBGRADE WIDTH	RUNNING WIDTH	POINT TO POINT	DRAINAGE
15 feet	12 feet	A to B	Shape to Drain
15 feet	12 feet	C to D	Shape to Drain
15 feet	12 feet	K to N	Shape to Drain
15 feet	12 feet	L to M	Shape to Drain

#### **IMPROVEMENT**

SUBGRADE WIDTH	RUNNING WIDTH	POINT TO POINT	DRAINAGE
15 feet 12 feet 15 feet 12 feet		C to E	Shape to Drain
		J to K	Shape to Drain

<u>CLEARING</u>. This work shall consist of clearing, removing, and disposing of all trees, Snags, Down Timber, brush, surface objects, and protruding obstructions within the clearing limits.

Where clearing limits have not been marked, the clearing limits shall extend 4 feet back of the top of the cutslope and 4 feet out from the toe of the fill slope, or as directed by STATE. Clearing debris shall not be placed or permitted to remain in or under any road embankment sections. Clearing debris shall not be left lodged against standing trees.

All danger trees, leaners, and Snags outside the clearing limits which could fall and hit the road shall be felled.

GRUBBING. This work shall consist of the removal or digging out of stumps and protruding objects.

All stumps shall be completely removed within the limits of required grubbing. Stumps overhanging cutslopes shall be removed. Grubbing debris shall not be left lodged against standing trees.

#### GRUBBING CLASSIFICATION.

Improvements and reconstructions - 4 feet back from the shoulder of the subgrade or ditch, whichever is widest, or as marked in the field.

<u>CLEARING AND GRUBBING DISPOSAL</u>. Scatter in stable locations through openings in the timber outside of the cleared right-of-way, except areas where end-haul is required. In areas where end-haul is required, clearing and grubbing debris shall be fully contained and hauled to a designated waste area. Clearing and grubbing debris shall be left in a stable location, and not left lodged against standing trees.

#### **EXHIBIT D**

#### FOREST ROAD SPECIFICATIONS

<u>EXCAVATION</u>. Excavation and grading shall not be done when weather and/or ground conditions are such that damage will result to existing subgrade or cause excessive erosion.

Unless road plans show otherwise, all roads shall be on a balanced cross section, except when the slope is over 60 percent, the road shall be on full bench for the width specified.

Suitable excavated material shall be used for the formation of fills, shoulders, and drainage structure backfills. Embankment materials shall be free of woody debris, brush, muck, sod, frozen material, and other deleterious materials.

Sidecast includes any road generated excess excavation material which is not essential as part of the road prism, is not compacted, and is below the roadway. Sidecast shall not be placed where it will enter a stream course. Leaving sidecast below the road is only permissible if specifically allowed in "Full Bench and End Haul Requirements" in this Exhibit.

All fills shall be machine compacted according to the "Compaction and Processing Requirements" in this Exhibit.

ROAD WIDTH LIMITATIONS. PURCHASER shall obtain advance written approval from STATE to construct the road to a greater width than specified.

<u>Curve Widening</u>. Widen the inside shoulder of all curves as specified in the plans or as follows: 400 divided by the radius of the curve equals the amount of extra width.


# **DRAINAGE**

<u>Subgrade</u>. Subgrade shall be crowned insloped at 4 to 6 percent as shown on the "Forest Road Specifications" table in this Exhibit.

Ditch. Construct "V shaped ditch 1 foot below subgrade as directed by STATE.

Ditchouts. Construct ditchouts to drain away from subgrade at locations marked in the field or as directed by STATE.

EXHIBIT E
WATERBAR SPECIFICATIONS



WATERBAR SPECIFICATIONS FOR CROSS DITCHING #298

EXHIBIT F
TANK TRAP SPECIFICATIONS

